


INSTALLATION INSTRUCTIONS

The #730 Channel is the upper guide. #771 Clip Guides grip the top edge of the panel and silence operation.

This assembly uses the #723 track. The #743 Shoes install on the bottom of the panel using #2021 Glazing Vinyl, and use the appropriate number of #752 nylon rollers for easy rolling action.

TYPICAL INSTALLATION



"H" - Height of Finished Opening


TO OBTAIN PANEL HEIGHT

Panel should be cut $1 \frac{7}{32}$ " less than the desired height of the finished opening.

TO OBTAIN PANEL WIDTH

Add $\frac{1}{2}$ " to opening width and divide by 2 for $\frac{1}{2}$ " overlap.

NOTE: Add 1" to opening width for 1" overlap.



THE ENGINEERED PRODUCTS CO.
FLINT, MI
www.epcohhardware.com



THE ENGINEERED PRODUCTS CO.
FLINT, MI

www.epcohhardware.com

- Silent, Smooth Operation
- Economical & Quick Install
- Satin Anodized Finish


LENGTH

_____ FT.

EZ GLIDE ALUMINUM SLIDING DOOR TRACK

ASSEMBLY NO.

14



package contains:

1 pc. #730 channel, #771 clip guides,
1 pc. #723 track, 2 #743 shoes, #752
nylon rollers, glazing vinyl, and
mounting screws

for $\frac{1}{4}$ " by-passing doors with
nylon rollers for:
**GLASS, PEGBOARD,
MASONITE, PLYWOOD, etc.**

INSTRUCTIONS ON REVERSE SIDE