

DÖKEN

Filled Glues

- For use with PVC, wood and high pressure laminate
- Good running properties
- Excellent wettability
- · Very good adhesion
- High bond strength
- · Good heat resistance

Unfilled Glues

- Cleaner running; glue pot stays cleaner longer
- Used on a wider variety of substrates
- · Good coverage
- Transparent

Descriptions:

Pellets

ETKS 205: Exceptionally strong, multi-purpose adhesive for automatic edgebanding equipment.

ETKS 208: Medium viscosity, multi-purpose EVA hotmelt with fast melting, spread and flow properties. ETKS 217: Low viscosity EVA hotmelt for automatic edgebanding equipment. Recommended for use in granular feed or quick step hotmelt systems.

ETKS 351: Medium viscosity multi-purpose EVA hotmelt for automatic edgebanding, soft forming equipment and automatic processing centers (BAZ) with direct application.

Cartridges

ETHKP 21: Standard grade, multi-purpose cartridge adhesive for Holzher edgebanders.

ETHKP 25: Premium grade, multi-purpose cartridge adhesive for Holzher edgebanders.

	Qty/lbs.	Color	*HPL	*PVC	Wood	Melamine
Pellets (Filled)						
ETKS205	55	Natural	•	•	•	•
ETKS208	55	Natural		•		•
ETKS217	55	Natural	•	•	•	•
Pellets (Un-Filled)						
ETKS351	55	Clear	•	•	•	•
<u>Cartridges (Filled)</u>						
ETHKP2	1 33	Natural		•	•	•
ETHKP25	5 33 essure lamir	Natural	olv viny	l chlorate	•	•