


SLUN

VERTICAL SWING LIFT-UP MECHANISM

- Unique swing mechanism provides a lift-assist feature to help lift doors and hold at the open position.
- Sleek, compact design provides maximum access.
- Easy installation.
- Adjustable arm mounting plate.
- Successfully passed for 30,000 open/close private cycle tests.



Designed to operate at room temperature
0°~40°C (32°~104°F).



VERTICAL SWING LIFT-UP MECHANISM




SLUN

LID SUPPORTS

VERTICAL SWING LIFT-UP MECHANISM



- Unique mechanism will help lift doors and hold at the open position.
- Sleek & compact design.
- Easy installation.
- Adjustable arm mounting plate.
- Patented LAPCON technology provides a smooth and quiet motion.
- Successfully passed 30,000 open/close private cycle tests.
- Recommended Door Size and Weight:
 - Width, 600~900 mm (23-5/8"~35-7/16")
 - Height, 390~450 mm (15-23/64"~17-23/32")
 - Weight, 2.8~5.8 kg (6.2~12.8 lbs)



Material	Finish/Color
Steel	Nickel
Plastic	Grey

Item No	Door Weight (kg)	Box (set)	Carton (set)
SLUN-3N	2.8~3.8 (6.2~8.4 lbs)	5	50
SLUN-4N	3.8~4.8 (8.4~10.6 lbs)		
SLUN-5N	4.8~5.8 (10.6~12.8 lbs)		

Guide Bar Length

Door Type	Cabinet Width (mm)	
	600 (23-5/8")	900 (35-7/16")
Solid Wood Door	535 (21-1/16")	835 (32-7/8")
Frame Door	551 (21-3/4")	851 (33-1/2")

*SLUB-835 (835 mm (32-7/8")) included unless specified.